

Digital Serial Interface Standard	Mapping Standard	Source Image Format	Image Format	CDH1813 input formats	PDM1383 input formats	PDM1284 input formats	DVD1xxx input formats	OBD1810 / OTx1xxx input formats	PVD1800 input formats	PMV1841 input formats
SD-SDI / 270 Mbit										
SMPTE 259M-2008	n.a.	SMPTE 125M								
Level C			525	✓	✓	✓	✓	✓	✓	✓
HD-SDI 1.5Gbit/s			625	✓	✓	✓	✓	✓	✓	✓
SMPTE 292-1:2012	n.a.	SMPTE 274M								
			1920 x 1080 / 60 / I	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 59.94 / I	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 50 / I	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 30 / P	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 29.97 / P	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 25 / P	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 24 / P	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 23.98 / P	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 25 / PsF	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 24 / PsF	✓	✓	✓	✓	✓	✓	✓
			1920 x 1080 / 23.98 / PsF	✓	✓	✓	✓	✓	✓	✓
		SMPTE 260M								
			1920 x 1035 / 60 / I	✓			✓	✓		
		SMPTE 296M								
			1280 x 720 / 60 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 59.94 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 50 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 30 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 29.97 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 25 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 24 / P	✓	✓	✓	✓	✓	✓	✓
			1280 x 720 / 23.98 / P	✓	✓	✓	✓	✓	✓	✓
		SMPTE 2048-2								
			2048 x 1080 / 30 / P	✓			✓	✓		
			2048 x 1080 / 29.97 / P	✓			✓	✓		
			2048 x 1080 / 25 / P	✓			✓	✓		
			2048 x 1080 / 24 / P	✓			✓	✓		
			2048 x 1080 / 23.98 / P	✓			✓	✓		
			2048 x 1080 / 30 / PsF				✓	✓		
			2048 x 1080 / 29.97 / PsF				✓	✓		
			2048 x 1080 / 25 / PsF				✓	✓		
			2048 x 1080 / 24 / PsF				✓	✓		
			2048 x 1080 / 23.98 / PsF				✓	✓		
		3GBit/s								
		SMPTE 424M-2006								
			YCbCr/4:2:2/12Bit not supported							
		SMPTE ST 425-1:2011	Level A							
			SMPTE 274M	1920 x 1080 / 60 / P	✓	✓	✓	✓	✓	✓
				1920 x 1080 / 59.94 / P	✓	✓	✓	✓	✓	✓
				1920 x 1080 / 50 / P	✓	✓	✓	✓	✓	✓
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 60 / I	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 59.94 / I	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 50 / I	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 30 / P	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 29.97 / P	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 25 / P	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 24 / P	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 23.98 / P	✓				
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 30 / PsF					
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 29.97 / PsF					
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 25 / PsF					
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 24 / PsF					
			RGB/YCbCrA/4:4:4:10	RGB/YCbCr/4:4:4:10/12	1920 x 1080 / 23.98 / PsF					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 60 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 59.94 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 50 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 48 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 47.95 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 30 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 29.97 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 25 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 24 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 23.98 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 30 / PsF					
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 29.97 / PsF					
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 25 / PsF					
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 24 / PsF					
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 23.98 / PsF					
			Level B-DL		Vers. 676 and later	Vers. 647 and later	Vers. 646 and later			
			SMPTE 274M	1920 x 1080 / 60 / P	✓	✓	✓	✓	✓	✓
				1920 x 1080 / 59.94 / P	✓	✓	✓	✓	✓	✓
				1920 x 1080 / 50 / P	✓	✓	✓	✓	✓	✓
			YCbCr/4:2:2/12Bit not supported							
			SMPTE 2048-2							
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 60 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 59.94 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 50 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 48 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 47.95 / P					
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 30 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 29.97 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 25 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 24 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	2048 x 1080 / 23.98 / P	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	1920 x 1080 / 30 / PsF	✓				
			RGB/4:4:4/12	RGB/4:4:4/12	1					

(*) HDMI output framerate has to be the same as the input framerate. For 1080p59 inputs the HDMI output has to be set to 1080p60 (p59 is supported with PMV1841 Version 746 and above).